Mobile Solar Generator GSR-111B



New roll-up type Photovoltaic Generator OS "Mobile Solar Unit" comes with new features.

Are you provided for disasters?

- Solar Sheet roll-up type
- Light weight(approx.2.8Kgs), easy carrying and easy installation
- Various optional equipments available for more applications
- It can recharge Smart Phones
- AC Adaptor for recharging is attached
- Low Voltage for safety



GSR-111B and Attachments (USB Adaptor, AC Adaptor)



Reference Time to run Electrical equipments

Items	Power Consumption (W)	Operational time (H)	
Mobile Phone	2	10	
Portable Radio	5	4	
Portable TV	5	4	
LED Lantern	4	5	
Digital Camera	1.6	12.5	
Video Camera	4	5	
Transceiver	3	6.7	
Loud Speaker	8	2.5	
Wireless Microphone	0.2	100	
Mobile Router	6	3.4	
Portable DVD Player	8	2.5	
Laptop PC 💥	30 ~ 50	0.5	

This chart shows the theoretical time when each of such electrical equipment is connected to GSR-111B. Actual time depends on conditions such as battery performance of such equipment.

The time for Laptop PC is measured when two GSR-111B units are connected.

It can increase the time by connecting more units or batteries by a connection unit (G-J01).

Video Camera Transceiever **Battery User-Replaceable Loud Speaker** Mobile Phone Built-in battery can be recharged Wireless Microphne Transceiver **LED Lantern** iPhone Portable Radio

for about 1,000 times, but userreplaceable in case of deterioration.

New Features

Digital Camera

Open Price

New Pilot Lamp for ease of checking battery status



Orange color is added to show the battery balance between 20 to 60%.

Main Cracification

main specifications			
Model	GSR-111B		
Dimensions	W510×H110×D85(mm) (except Handle portion)		
Weight	Approx.2.8Kgs		
Built-in battery	Ni-MH (Nickel Metal Hydride) 2.0Ah/12V DC Appox.20Wh		
Output Power	20W(Max 24W) / Built-in battery, 12W(Max 16W) Solar Sheet		
Built-in batter charging time Approx.	5hours by Solar, Approx. 4hours by AC Adaptor		
Water Proof	IP13 (Main unit only)		
Operational Environment	Temp. : -10°C ~ 60°C Humidity : Less than 85%RH (Non-condensed)		

Portable TV

Attachments

■ AC Adaptor



Model: G-A03 This allows charging built-in battery from AC inlet at home.

■USB Output Adaptor




Model: G-A02 This has 2 ports and can charge Smart phones

except some special phones



More optional equipments, more applications !!

■ For example, with a connection unit-



Laptop PC

Solar Sheet GSR-010N
(will be released soon)

External Battery

GSB-01



Crystal TV (22' type)

■ External Battery

Pre-charged Battery can be carried alone



Connection Unit G-J01
Car Cigar type Plug,
12V output

External Battery GSB-01

External Battery GSB-01

GSR-110B can be connected.

GSR-111B can be connected.

DC/AC Inverter(G-A04) for 100V AC output.

Emergency Disaster Set You can use this as soon as you purchase. <Set items > GSR-111B-S1 also released. (Open Price)

GSR-111B unit (incl. attachments)

Rechargeable Lantern (G-L01) / Dimensions:H195 x φ 105mm, LED:12 (6 x 2 laws),

Continuous lighting time for 50hours、Weight: Approx.0.6Kgs

USB 4 ports Hub / USB Ver.2.0 compliant、Weight: Approx.0.06Kgs

Mobile Phone USB Cable Set / Docomo(FOMA、mova) • au (WIN、CDMA) • Softbank 3G supported、Weight : Approx. 0.03Kgs



Options

Product Name	External Battery	Connection Unit	Connection Cable	Battery Pack	DC/AC Inverter
Appearance	8	GARGAR		THE COLUMN TWO IS NOT	
Model	GSB-01	G-J01	G-C01	G-B01	G-A04
Dimensions	W115×H100×D85	W85×H62×D95	L=1700 %	W77×H34×D34	W100×H45×D75
Weight(Kg)	Approx.0.8	Approx.0.3	Approx.0.04	Approx.0.3	Approx.0.4
Usage/ Characteristics	* Nickel Metal Hydride (Ni-MH) 2.0Ah/DC12V Approx.20Wh * Built-in Battery replaceable * Charging Time : Approx.5hours / Solar Power Approx.4hours / AC Adaptor * Water Proof : IP13	Power up by connecting multiple Mobile Solar and External Battery units * Up to 6units to input * Output : Max.100W (6units) * Connectable units GSR-110B, GSR-111B, GSR-010N(on sale soon) GSR-01 External battery * Water Proof: IP13	* Connection cable for Connection Unit and External Battery. * Cigar Plug(with Fuse) for the connection between Mobile Solar Units. * Excl. Plug	Replace Battery for GSR-111B and External Battery * Battery : Nickel Metal Hydride 2.0Ah/DC12V Approx.20Wh	DC/AC Inverter to convert DC output to AC100V to use home equipment. * Input Voltage 12V Cigar Plug Type * Output AC/100W (55Hz) DC5V (500mA) USB
Attachments	Connection Cable (with Spare Fuse)	Connection Cable (with Spare Fuse)	Spare Fuse (2A)	_	Spare Fuse (2A)
Price	Open	Open	Open	Open	Open

OS CO., LTD.



Global Marketing Division International Operation OS Tokyo Bld.3-25-18 Ayase, Adachi-ku, Tokyo,120-0005, Japan Tel.+81-3-5697-0980 Fax.+81-3-5697-0990 Http://www.os-worldwide.com